

Continuously Variable Transmission (CVT) Fluid fitted with chain or belt Technosynthese®

### TYPE OF USE

High performance Technosynthese<sup>®</sup> fluid specially engineered for Continuously Variable Transmission (CVT) gearbox type. Suitable for use in a wide range of vehicles fitted with CVT gearboxes using either chain/pulleys or belt/pulleys design. Especially suitable for vehicles from American car makers GM, FORD, CHRYSLER,..., Asian car makers HONDA, HYUNDAI, KIA, LEXUS, INFINITI, MITSUBISHI, NISSAN, SUBARU, TOYOTA,... or European car makers AUDI, BMW, CITROËN, MERCEDES, PEUGEOT, RENAULT, ...

Attention, not recommended for CVT unit fitting hybrid vehicles. Before use always refer to the owner manual or handbook of the vehicle.

#### **PERFORMANCES**

MOTUL MULTI CVTF is a high tech multi vehicles CVT fluid suitable for a wide range of CVT-equipped passenger cars, including belt-CVT and chain-CVT design.

Thanks to its exclusive and dedicated formula, MULTI CVTF:

- Allows fuel economy for cars fitted with CVT automatic gearboxes by providing optimum metal-to-metal friction.
- Provides high anti-shudder performance to avoid engine vibrations for increased comfort.
- Protects gears that are more and more numerous, compact and heavily loaded.
- Gives superior automatic transmission response through smooth shift feel and reduced shift time lag.
- Improves CVT reaction at cold temperature.
- Extends life time duration due to high shear stability at hot temperature and high oxidation resistance.
- Increases wear protection of belt, chain and pulleys.
- Anti-corrosion, anti-foam.

#### **RECOMMENDATIONS**

Can be mixed only with similar lubricants.

Oil change: according to manufacturer's recommendations and adapt according to your own use.

Not recommended for CVT unit fitting hybrid vehicles.

Before use always refer to the owner manual or handbook of the vehicle.

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - AUBERVILLIERS CEDEX - BP 94 - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com



Continuously Variable Transmission (CVT) Fluid fitted with chain or belt  $\label{eq:continuously} \textbf{Technosynthese}^{\circledR}$ 

### **PROPERTIES**

· · · · · · · · · · · · · · · · · · ·		
Color	Visual	Blue
Density at 20°C (68°F)	ASTM D1298	0.852
Viscosity at 40°C (104°F)	ASTM D445	34.3 mm²/s
Viscosity at 100°C (212°F)	ASTM D445	7.2 mm²/s
Viscosity Index	ASTM D2270	180.0
Flash point	ASTM D92	210.0 °C / 410.0 °F



Continuously Variable Transmission (CVT) Fluid fitted with chain or belt  $\label{eq:continuously} \textbf{Technosynthese}^{\circledR}$ 

OF REDECRIANCES		
OE PERFORMANCES	T	
AUDI	Multitronic, TL 52 180, TL 52 516	
BMW	83 22 0 136 376, 83 22 0 429 154, EZL 799, EZL 799 A	
CHRYSLER 	CVTF+4	
CITROËN	9735 EF, Elfmatic CVT, Elfmatic CVT MV	
DAIHATSU	CVTF 3320	
DODGE	05191184AA, CVTF+4, NS-2	
DS (CAPSA)	9735 EF, Elfmatic CVT, Elfmatic CVT MV	
FIAT	9.55550-AG4, CVT23, CVT30, MERCON C, Tutela Car CVT N.G, Tutela GI/Z, WSS M2C 928 A, WSS M2C 933 A, XT-7QCFT	
GENERAL MOTORS	DEX-CVT	
HONDA	0826099905HE, 087009006, CVT-F, HCF-2, HMMF (Honda Multi Matic Fluid)	
HYUNDAI	Genuine CVTF, SP-CVT 1, SP III	
INFINITI	NS-1, NS-2, NS-3	
JEEP	05191184AA, CVTF+4, NS-2, VTF	
KIA	SP-CVT 1, SP III	
LEXUS	CVTF 3320, CVT FE, TC	
LIFAN	CVT	
MAZDA	CVTF 3320	
MERCEDES-BENZ	A 001 989 46 03, MB 236.20	
MG	EM-CVTF	
MINI	83 22 0 136 376, EZL 799, EZL 799 A	
MITSUBISHI	Dia Queen CVTF-J1, Dia Queen CVTF-J4, MZ313973, SP	
NISSAN	999MP-NS200P, NS-1, NS-2, NS-3	
PEUGEOT	9735 EF, Elfmatic CVT, Elfmatic CVT MV	
RENAULT	Elfmatic CVT, Elfmatic CVT MV	
ROVER	EM-CVTF, Unipart Transmatic ATF	
SATURN	22688912, DEX-CVT	
SUBARU	CVT TR580, CVT TR690, High Torque CVT, iCVTF, K0425Y0710, K0425Y0711, Lineartronic CVTF, Lineartronic II, NS-2	
SUZUKI	CVTF 3320, CVT Green 1, CVT Green 2, NS-2, TC	
TOYOTA	CVTF 3320, CVT FE, TC	
VOLVO	CVTF 4959	
vw	G 052 180, G 052 516	
PRODUCTS		
ELF	matic CVT, matic CVT MV	
ESSO	EZL 799, FN1975	
IDEMITSU	CVTF-EX1, CVTF-EX-2	
	I .	

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - AUBERVILLIERS CEDEX - BP 94 - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com



Continuously Variable Transmission (CVT) Fluid fitted with chain or belt  $\label{eq:continuously} \textbf{Technosynthese}^{\circledR}$ 

MOBIL	CVTF 3320
MOPAR PARTS	CVTplus4
PSA Groupe	9735 EF, Elfmatic CVT, Elfmatic CVT MV
PUNCH	CVTF-EX1, CVTF-EX2
SHELL	Green 1V